- 1 -

TITLE OF INVENTION

METHOD OF AUTOMATICALLY GENERATING THE

STRUCTURES FROM MASK LAYOUT

FIELD OF THE INVENTION

The present invention relates to a

method for generating a three-dimensional

structure of a liquid crystal cell, which can be

employed for designing the LCD panel by

predicting the dynamics of a liquid crystal

pixel, and a computer software system utilizing

the same.

More particularly, the present invention

relates to a method for estimating a three-

dimensional structure comprising a plurality of

material layers between upper and lower

substrates through computer simulation from the

a mask layout input data, wherein the three-

dimensional structure is defined through the

computer simulation by depositing the material

layers on the upper and lower substrates acting

as reference base planes, respectively, and

sandwiching an intermediate insertion layer

between the upper and lower substrates with the

material layers thereon facing each other, in

particular, in the case where at least one of the material layers has a tapered region (which will be referred to as an "tapered material layer"), which is not parallel to the upper and lower substrates and is inclined to the base planes.

A liquid crystal display is a display apparatus generally constructed such that a liquid crystal material is filled in a space between a lower substrate having a thin film transistor, a pixel electrode and the like formed thereon and an upper substrate having an opposite electrode, a color filter, and the like formed thereon.

For the computer simulation of the liquid crystal display, a conventional software system for two-dimensional computer simulation employs a method of defining polygons as cross-sectional shapes of the liquid crystal cell in order to define a three-dimensional structure of the liquid crystal cell, and thus it is difficult for the conventional software system to define the three-dimensional structure of the liquid crystal cell.

SUMMARY OF THE INVENTION

Accordingly, it is an object of the present invention to provide a method for producing a three-dimensional structure from a mask layout.

It is another object of the present invention to provide a method for defining a three-dimensional structure of a liquid crystal cell constituting a liquid crystal display.

It is yet another object of the present invention to provide a system for defining the three dimensional structure of the liquid crystal cell constituting the liquid crystal display.

In accordance with one aspect of the present invention, the above and other objects can be accomplished by the provision of a method for defining a three-dimensional structure of a liquid crystal cell, comprising the steps of: reading mask layout information for the liquid crystal cell; inputting a deposition sequence of material layers constituting the liquid crystal cell by use of the mask layout information for the liquid crystal cell; and defining the three-dimensional structure of the liquid crystal cell by use of the mask layout information in which a mask layout consists of polygons.

In accordance with another aspect of the

present invention, a system for defining a three-dimensional structure of a liquid crystal cell is provided, comprising: a preparation module for mask layout information; an input module for a deposition sequence of material layers constituting the liquid crystal cell; a change module for polygons constituting the mask layout; and a creation module for a three-dimensional structure of the liquid crystal cell.

BRIEF DESCRIPTION OF THE DRAWINGS

Further features of the present invention will become apparent from a description of a method for defining a three-dimensional structure of a liquid crystal cell, which can be applied to manufacturing a computer simulation analyzer for predicting dynamic kinetics of a liquid crystal display, and a computer software system utilizing the same taken in conjunction with the accompanying drawings of the preferred embodiment of the invention, which, however, should not be taken to be limitative to the invention and are for explanation and understanding only.

In the drawing:

FIG.1 is a flow diagram illustrating a

method for defining a three-dimensional
structure of a liquid crystal cell in accordance
with a preferred embodiment of the present
invention.

FIG.2 is a flow diagram illustrating a
preferred embodiment of a process for inputting
a deposition sequence of material layers
constituting the liquid crystal cell by use of
mask layout information for the liquid crystal
cell in the method of the invention.

FIGS. 3 to 7 show sequential steps of
the method for defining the three-dimensional
structure of the liquid crystal cell in
accordance with the embodiment of the invention.

FIG.8 is a constitutional view of a
system for defining a three-dimensional
structure of a liquid crystal cell in accordance
with a preferred embodiment of the invention.

FIG. 9 is a view illustrating a
preferred embodiment of a preparation module for
mask layout information.

FIG. 10 is a view illustrating a
preferred embodiment of an input module for a
deposition sequence of material layers
constituting the liquid crystal cell, which is
exhibited when selecting a button for defining
the three-dimensional structure.

- 6 -

FIG. 11 is a view illustrating a preferred embodiment of an input module for the information of material layers, which is exhibited when selecting a button for adding a new material layer.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT
OF THE INVENTION

Embodiments of the present invention will now be described in detail with reference to FIGS. 1 and 7.

FIG.1 is a flow diagram illustrating a method for defining a three-dimensional structure of a liquid crystal cell according to the invention. Referring to FIG. 1, the method comprises the steps of reading mask layout information for the liquid crystal cell in which a mask layout consists of polygons (S110); inputting a deposition sequence of material layers constituting the liquid crystal cell by use of the mask layout information for the liquid crystal cell (S120); and defining the three-dimensional structure of the liquid crystal cell by use of the mask layout information (S130).

According to the preferred embodiment of

the invention, the mask layout information for the liquid crystal cell structure is provided in the form of an electronic file produced by a mask layout producing system.

FIG.2 is a flow diagram illustrating a preferred embodiment of a process for inputting a deposition sequence of material layers constituting the liquid crystal cell by use of the mask layout information for the liquid crystal cell structure in the method of the invention. Referring to FIG. 2, the process comprises the steps of defining characteristics of a liquid crystal layer (S210); defining the deposition sequence of the material layers respectively formed on upper and lower substrate with the liquid crystal layer provided as a center layer between the upper and lower substrates (S220); and storing information of the material layers deposited in the liquid crystal cell (S230).

According to the preferred embodiment of the invention, the characteristics of the liquid crystal layer may be determined by a method of defining a kind of liquid crystal material and a thickness of the liquid crystal layer with regard to the basically produced liquid crystal layer.

According to the preferred embodiment of
the invention, the step of defining the
deposition sequence of the material layers on
the upper and lower substrates with the liquid
crystal layer provided as the center layer
between the upper and lower substrate may be
realized by a process of sequentially defining
the material layers constituting the upper and
lower substrates from the lower substrate to the
upper substrate in the vertical direction with
the liquid crystal layer basically produced as
the center layer between the upper and lower
substrates, and alternatively, by a process of
defining a new material layer, which is inserted
between the previously defined material layers.
The new material layer may be defined using a
name of the material layer, a kind of the
material, a thickness of the material layer, a
name of the mask, a kind of positive or negative
mask, an angle of side surface, and a kind of
the substrate.

According to the preferred embodiment of
the invention, the information of the deposited
material layer in the liquid crystal cell may be
directly stored in a memory of a computer.
Alternatively, the information of the deposited
material layer may be provided as an electronic

file in a storing media, such as a hard disk
drive, for the computer.

FIGS. 3 to 6 show a preferred embodiment
of a method for defining the three-dimensional
structure of the liquid crystal cell of the
invention. Referring to FIG. 3, as the
preferred embodiment of the mask layout
information for defining the three-dimensional
structure, the information of the mask layout
consisting of a region 300 for defining the
three-dimensional structure, a first mask 310
and a second mask 320 is shown.

Referring to FIG. 4, the first mask 310
is a mask to which a taper angle is not
designated, and the second mask 320 is a mask to
which the taper angle is designated. With the
second mask 320 to which the taper angle is
designated, a divided polygon 321 is formed by
dividing an internal area of a polygon of a mask
layout object along edges overlapped by the
polygon of the mask layout object and a polygon
of another mask. FIG. 5 shows the three-
dimensional structure of the mask of FIG. 4.

Referring to FIG. 6, a first material
layer 350 having a predetermined thickness is
formed by use of the region 300 for defining the
three-dimensional structure, a second material

layer 360 having a predetermined thickness is formed on the first material layer 350 by use of the first mask 310, and a third material layer 370 is formed on the three-dimensional structure consisting of the first material layer 350 and the second material layer 360 by use of the second mask 320 having the divided polygon 321.

According to the preferred embodiment of the invention, a thickness of each material layer may be designated by a user. According to the preferred embodiment, the second material layer 360 may be formed by expanding the structure of the first mask 310 upward by a thickness designated by the user from an upper surface of the first material layer 310.

According to the preferred embodiment of the invention, in order to form the third material layer 370, the structure of the second mask 320 is initially formed as a lower surface of the third material layer 370 on an exposed upper surface of the three-dimensional structure consisting of the first and second material layers 350 and 360, an upper surface of the third material layer 370 is produced by expanding the structure of the divided polygon 321 upward by a thickness designated by the user from the lower surface of the third material

layer 370, and side surfaces of the third
material layer 370 are then formed by connecting
apexes of the lower surface of the third
material layer 370 to corresponding apexes of
the upper surface of the third material layer
370.

Referring to FIG. 7, in addition to the
three-dimensional structure of the lower
substrate consisting of the first, second and
third material layers 350, 360 and 370, a fourth
material layer 380 constituting the upper
substrate is formed at a position displaced a
thickness of the liquid crystal material
designated by the user from the lowest point of
the upper surface of the lower substrate in the
vertical direction, and a fifth material layer
390 is formed between the lower surface of the
upper substrate and the upper surface of the
lower substrate. According to the preferred
embodiment of the invention, the fifth material
390 filling a space between the lower substrate
and the upper substrate is defined as the liquid
crystal material.

FIG. 8 is a constructional view of a
system for defining the three-dimensional
structure of the liquid crystal cell of the
liquid crystal display according to the

invention. Referring to FIG. 8, the system 400
for defining the three-dimensional structure of
the liquid crystal cell comprises a preparation
module 410 for mask layout information, an input
module 420 for information of a deposition
sequence of material layers constituting the
liquid crystal cell, a creation module 430 for
the three dimensional structure of the liquid
crystal cell, a definition file 440 for the mask
layout, and an information file 450 for the
deposition sequence of material layers in the
liquid crystal cell.

FIG. 9 is a view of a preferred
embodiment of the preparation module 410 for the
mask layout information. Referring to FIG. 9,
the preparation module 410 comprises a
simulation region setting button 501, a three-
dimensional structure defining button 502, a
mask layout preparation portion 510, and a mask
management portion 520. The mask management
portion 520 has a function for selecting a mask
521 from a mask list while exhibiting the mask
list included in the definition file 440 for the
mask layout, and the simulation region setting
button 501 has a function for drawing a mask
object 511 on the mask selected from the mask
list 520. The simulation region setting button

501 has a function for setting the simulation
region 530 in the mask layout producing portion
510. The mask management portion 520 has a
function for allowing the input module 420 for
the information of deposition sequence of
material layers constituting the liquid crystal
cell to be executed.

FIG. 10 is a view illustrating a
preferred embodiment of the input module 420 for
the information of the deposition sequence of
material layers constituting the liquid crystal
cell, which is exhibited when selecting the
three-dimensional structure defining button 502.
Referring to FIG. 10, the input module 420 for
the information of deposition sequence of
material layers constituting the liquid crystal
cell comprises an information viewer 610 for the
deposition sequence of the material layers, an
insert button 620 for adding a new material
layer, a delete button 630 for deleting the new
material layer selected from the information
viewer 610 for material layers, an execution
button 640 for generating the three-dimensional
structure, an opening button 650 for reading the
information of material layers, and a save
button 660 for saving the information of
material layers.

FIG. 11 is a view illustrating a preferred embodiment of an input module 700 for the information of material layers, which is exhibited when selecting the insert button 620 for adding the new material layer. Referring to FIG. 11, the input module 700 for the information of material layers comprises a material selecting portion 710, an input portion 720 for a thickness of the material layer, a mask selecting portion 730, a mask characteristic setting portion 740, an upward-insert button 750 for adding a new material layer above the selected material layer, a downward-insert button 760 for adding a new material layer under the selected material layer, and a close button 770 for closing the input module 700 for the information of material layers.

The mask characteristic setting portion 740 comprises a mask selecting portion 741 between a positive mask and a negative mask, a taper angle input portion 742 for inputting a taper angle at edges of the material layer when depositing the material layers using the mask, and a selection portion 743 for selecting whether a side surface of the material layer using the mask is formed with a sharp taper

angle or a smooth taper angle.

As apparent from the above description, the invention provides the system for defining the three-dimensional structure of the liquid crystal cell of the liquid crystal display, which comprises the preparation module for the mask layout information, the input module for the deposition sequence of material layers in the liquid crystal cell, and the definition module for defining the three-dimensional structure of the liquid crystal cell, and the method for defining the three-dimensional structure of the liquid crystal cell, which comprises the step of inputting the deposition sequence of material layers of the liquid crystal cell using the mask layout information for the liquid crystal cell and the step for defining the three-dimensional structure of the liquid crystal cell using the information of the mask layout consisting of the polygons, thereby constituting the structure definition system for executing computer simulation for the liquid crystal cell of the liquid crystal display.

Although the invention has been illustrated and described with respect to exemplary embodiments thereof, it should be understood by those skilled in the art that

- 16 -

various other changes, omissions and additions
may be made therein and thereto, without
departing from the spirit and scope of the
present invention.

Therefore, the present invention should
not be understood as limited to the specific
embodiment set forth above but to include all
possible embodiments within a scope encompassed
and equivalents thereof with respect to the
features set forth in the appended claims.